## 海景


MODE

## GC20568 系列

## 直驱式微油自动剪线高速双针平缝机

HIGH SPEED TWO NEEDLE SEMI-DRY DIRECT DRIVE NEEDLE

GC20568-MDZ GC20568-HDZ GC20568-BDZ



GC20568-MDZ 直驱式微油自动剪线高速双针平缝机



301







本系列机型设计采用小型内置式、大功率、大扭矩的 伺服电机直接驱动。针杆部位采用微油润滑。双直针、立式自动润滑旋梭勾线,构成两行平行的双线锁式线迹。由于机头颚部增高,机针部位视线开阔,更方便小型物件的缝制。针杆摆动与送布牙同步送料,能确保线迹均匀及防止缝料滑移。剪线机构设计合理,剪线动作稳定可靠。外观造型简洁流畅、色彩清新时尚。配置的电脑控制系统性能优异,通过操作面板可方便地进行各种缝纫模式的选择。适用于缝制衬衫、制服、大衣、内衣、床上用品等。

GC20568-MDZ is designed with needle bar semi dry and mini builtin powerful servo motor for direct drive, which can start and stop quickly with accurate positioning. With two straight needles and self-lubricated vertical-axis rotating hook, it can produce two parallel lines of lockstitch. Higher machine arm gives a wider view to needle position and is convenient for stitching small articles. Synchro feeding of needle bar and feed dog assures even stitches and prevents materials being sewn from displacement. It has reliable thread trimming performance and a novel appearance. The high efficient digital control system conveniences the setting of different sewing modes by operating panel. It is available for stitching garment, bedding, upholstery, etc.

特殊规格针间距请在订货时指定 Please specify for special needle gauge when ordering





型 号 Model	GC20568-MDZ	GC20568-HDZ	GC20568-BDZ
用途 Applicaticon	薄料、中厚料 Light to medium heavy weight	中厚料、厚料 Medium heavy weight to heavy weight	
最高缝速 Max.sewing speed	4000 r. p.m.	3000 r. p.m.	
线迹长度 Stitch length	0 - 5 mm	0 - 7 mm	
针杆行程 Needle bar stroke	33.4 mm		
压脚提升 Presser foot lift	手动 7mm 膝控 13mm By hand 7mm By knee 13mm		
机针 Needle size	DP×5 11"-14"	DP×5 18*-22*	
旋梭 Rotating hook	日 功 消		自动润滑剪线用大旋梭 Auto lubrication large hook for trimmer
针间距 Needle gauge	标准 6.4 mm 特殊 3.2 4.8 9.5 mm Standard 6.4 mm special 3.2 4.8 9.5 mm		
操作空间 Working space	264 × 126 mm		
电动机 Motor	220 伏 550 瓦伺服电机 220V 550W Servo motor		