油泵

MODEL

GC24528-B

立柱式针杆离合双针平缝机

TWO NEEDLE POST BED NEEDLE FEED HEAVY DUTY LOCKSTITCH SEWING MACHINE WITH SPLIT NEEDLE BAR

HIGHLEAD CANADA WWW.HIGHLEADCANADA.COM



301 x2








本机是海菱高台机的系列产品。双立柱式缝台,大型立式旋梭,针杆采用机械式分离机构。上下轴用滚珠轴承支承,同步齿形带传动,旋钮式针矩调节装置及杠杆式倒顺缝装置。柱式缝台高度 178 毫米,可根据针位不同方便的调整。操作空间宽敞,回转灵活。由于采用针杆摆动与送布牙同步送料的方式,故特别适用于几层不同质地材料的缝制,可防止缝料层之间的滑移,线迹均匀美观。

This machine is a product of Highlead brand post bed lockstitch sewing machine series. It is designed with post bed, large vertical rotating hook, split needle bar, ball bearings for upper and lower shaft, cog belt, dial-type stitch regulator and lever-type reverse feeding mechanism. The 178mm post bed can be easily adjusted for different needle gauges. With synchronized feeding by needle bar and feed dog, it is specially available for stitching several layers of different texture material, as well as for preventing displacement between layers.

特殊规格针间距请在订货时指定 Please specify for special needle gauge when ordering



GC24528 -B 立柱式针杆离合双针平缝机





| 最高缝速 Max.sewing speed | 2000 r.p.m. |
|------------------------------|--|
| 线迹长度 Stitch length | 0-5 mm |
| 针杆行程 Needle bar stroke | 33.4 mm |
| 压脚提升 Presser foot lift | 手 动 By hand 7mm 膝 控 By knee10mm |
| 机针 Needle size | DP × 5 11"-14" |
| 针间距 Needle gauge | 4.8mm (标准 Standard) 特殊 Special 6.4 8 9.5 12.7mm |
| 旋 梭 Rotating hook | 立式自动润滑大旋梭 Auto lubricated large vertical hook |
| 缝台高度 Highness of post-bed | 178 mm |
| 润滑方式 Lubrication | 半自动润滑 Semi-auto lubricated |
| 电动机 Motor | 370 瓦缝纫机专用电机 370W Clutch motor |