GC24618 (HG9910) 系列

立柱式滚轮综合送料平缝机

WITH POLLER

GC24618(HG9910) GC24618-1(HG9920) GC24618-D HG9910-BT GC24618-1D HG9910-D HG9910-B HG9920-D



本机是海菱高台机系列中的高档产品。分单针及双针 两种。采用连杆挑线、驱动式轮形压脚、轮形送布牙与机针 同步送料,立式旋梭勾线,形成双线锁式线迹。上下轴用高 精度同步齿形带传动; 主要部位均采用滚针轴承或滚珠轴 承;按钮式针距调节机构;立柱式缝台。本机线迹美观,运 转轻滑,缝纫性能极佳。特别适合于缝制高档皮鞋、包袋、 手套、帽子等弧形中厚料物品。

GC24618(HG9910) 型单针立柱式滚轮综合送料平缝机 GC24618-1(HG9920) 型双针立柱式滚轮综合送料平缝机 GC24618-D 型自动剪线单针立柱式滚轮综合送料平缝机 GC24618-1D 型自动剪线双针立柱式滚轮综合送料平缝机 HG9910-B 单针立柱式滚轮综合送料平缝机(可倒缝) HG9910-BT 单针立柱式自动剪线滚轮综合送料平缝机(可倒缝) HG9910-D 单针立柱式自动剪线滚轮综合送料平缝机(可倒缝) HG9920-D 双针立柱式自动剪线滚轮综合送料平缝机(可倒缝)

This machine is sub-classed into single needle and two needle versions. It is designed with link lever thread take-up vertical rotary hook, compound feed by driven roller presser foot, roller feed dog and needle, to produce lockstitch. It uses precise cog belt for driving arm shaft and hook shaft, knob type stitch regulator and post sewing bed. With needle bearing and ball bearing used in the key moving positions, the user can obtain elegant stitches, smooth and quiet running and excellent sewing performance. So it is oespecially available for sewing on medium heavy weight articles with small radius, such as superior leather shoes, handbags, gloves,caps,etc.It ensures you easy daily maintenance

GC24618(HG9910) Single needle post-bed compound feed lockstitcher with roller GC24618-1(HG9920) Twin-needle post-bed compound feed lockstitcher

GC24618-D Single needle post-bed compound feed lockstitcher with roller

and auto thread trimmer GC24618-1D Twin-needle post-bed compound feed lockstitcher with roller and auto thread trimmer HG9910-B Single needle post-bed compound feed lockstitcher with roller

HG9910-B Single needle post-bed compound feed lockstitcher with roller and back tacking
HG9910-BT Single needle post-bed compound feed lockstitcher with roller, back tacking and auto thread trimmer
HG9910-D Single needle post-bed compound feed lockstitcher with roller, back tacking and auto thread trimmer
HG9920-D Twin-needle post-bed compound feed lockstitcher with roller, back tacking and auto thread trimmer

· HIGHLEAD · * im 187 EN

GC24618 立柱式滚轮综合送料平缝机





型号 Model		GC24618 (HG9910)	GC24618-1 (HG9920)	GC24618-D	GC24618-1D	HG9910-B	HG9910-BT	HG9910-D	HG9920-I
最高缝速 Max.sewing speed		3000 r.p.m.				2000 r.p.m.		3000 r.p.m.	
线迹长度 Stitch length		1.3-7mm	1.3-4.8mm	1.3-7mm	1.3-4.8mm	0-5	mm	1.3-7mm	1.3-4.8m
针杆行程 Needle bar stroke		38mm				41 mm		38mm	
压脚提升 By har		7mm							
Presser foot lift	膝控 By knee	14mm			12mm		14mm		
缝台高度 Post height		178mm							
送布牙 Feed dog		驱动式轮形齿 Driven roller type							
机针 Needle size		DP × 5 11 [#] -14 [#]							
针间距 Needle gauge		-	2.4 mm	_	2.4mm		_	2.4mi	
倒缝装置 Reverse feeding system		-				V			
自动剪线装置 Thread trimming		-	_	,	~			√	
旋梭 Rotating hook		立式旋梭 Vertical hook							
润滑方式 Lubrication		手工润滑 Manual							
电动机 Motor		1400 370W Clu	N机专用电机 转/分 utch motor ir.p.m.	伺服 220V	电机	170 瓦建树机 专用电机 220 伏 550 瓦伺服 220V550W Servo molor			